



JK LAKSHMIPLAST

SMART WALL PRIMER

SMART EXTERIOR WALL PRIMER



सुंदरता गारंटीड

JK Lakshmiplast Smart Exterior Wall Primer is a water-based undercoat to emulsions suitable for exterior walls.


PRODUCT BENEFITS



Excellent Coverage
120 to 140 sq ft/ltr.



Ultra-White &
Opaque with
Smooth Finish.



Does not Chalk
& can be Applied
on Adequately Cured
Fresh Plaster.



Gives Superb
Adhesion to Top
Coat Emulsion.



Excellent Top
Coat Appearance.



0% Water Curing
Required.

PRODUCT FEATURES

- 100% acrylic latex & co-polymer based
- Low VOC (volatile organic compound)
- Low odour
- Extra TIO₂ (Titanium dioxide) added for maximum coverage and increased whiteness

TECHNICAL SPECIFICATIONS

- Coverage – 120-140 sq ft/ltr
- Drying Time – 3-4 Hrs
- Flash Point – NA
- Specific Gravity – 1.4
- Pot Life – 24 Hrs
- Shelf Life – 24 months from the date of manufacture in original tightly closed containers away from sunlight & excessive heat

AREA OF USAGE

- Interior & exterior cement plaster
- Concrete
- Asbestos sheets
- Ceilings
- Existing painted surfaces

DIRECTION FOR USE

- Prepare the surface smooth & wipe clean & dry
- JK Lakshmiplast Smart Exterior Wall Primer can be thinned with water in 1:1 ratio by volume
- Apply 1st coat & allow to dry for 3-4 hours
- If needed smoothen the surface again & let it dry for 3-4 hours
- Apply next coat of primer & get a smart finish to reduce consumption of top coat
- Allow it to dry for 3-4 hours make it smooth & now surface is ready for the top coat

FOR BEST RESULTS: Before applying primer, prepare the surface by using Available in 1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr *Subject to availability.

Customer Helpline: 1800 102 5097 www.jklakshmicement.com

www.instagram.com/jklakshmicementofficial www.facebook.com/JKLakshmiCementLtd

