



JK LAKSHMIPLAST
SMART WALL PUTTY

PRESENTING

SMART WALL PUTTY

COLOUR KI BEAUTY



Made from
high purity
white cement

Water resistant

Smooth finish

For exterior & interior



JK LAKSHMIPLAST SMART WALL PUTTY

JK Lakshmi Cement Ltd., a member of the prestigious J.K. organization, believes in offering complete construction solutions to the customers. To meet this goal, the Company offers several products such as- Cement in various grades, different varieties of Ready-Mix Concrete, Gypsum Plaster, Gypsum Bond, AAC Blocks, Mortars etc..

Continuing this endeavour, company has now added JK LAKSHMIPLAST SMART WALL PUTTY as a contemporary solution to cover unevenness and pin holes on surfaces. It is typically used as filler/ sealing agent and applied before painting of the wall in both Internal&External applications. Being made using high purity cement and high-strength polymers, Smart Wall Putty gives a strong base to surface which prevents paints from flaking.

JK SMART WALL PUTTY is manufactured under strict quality controls which offers significant advantages during usage.



SMART FEATURES

- Made from High Purity White Cement
- High Strength Polymer based for strength and water resistance
- Ultra precision grinding results in superior fineness



SMART BENEFITS

- High strength after drying ensuring long life of paints
- Excellent whiteness to ensure retaining for long beauty of colours
- Prevents Flaking of paints
- Fungi resistant.
- Can be applied on moist surfaces and on internal and external surfaces
- Eco friendly, it does not contain lead, oil or toxic material
- Smooth finish results in reduced paint consumption



TECHNICAL SPECIFICATION

| PROPERTIES | Tensile adhesion strength @ 28 days | Compressive strength @ 28 days | Initial setting time | Final setting time | Water demand* |
|---------------|-------------------------------------|--------------------------------|----------------------|--------------------|---------------|
| UNITS | N/mm ² | N/mm ² | min | min | Percentage(%) |
| SPECIFICATION | ≥ 2 | ≥ 7 | ≥ 100 | ≤ 500 | 30-40 |

*Depends on climate



METHOD OF APPLICATION

- Make Surface clean by removing dust, etc.
- Extract smart wall putty powder with a dry vessel
- Add adequate water (30% -40%) based on climate conditions.
- Mix well to make a uniform paste
- Apply this paste on the cleaned surface with trowel
- After drying of 1st coat, if needed, apply 2nd coat.
- Now surface is ready for painting, colouring etc.



STORAGE

JK LAKSHMIPLAST SMART WALL PUTTY should be stored in a dry place

- Use it within 6 months from the date of manufacturing.
- Store the bags on dry platform.



PRECAUTION DURING APPLICATION

- Tools to be used in mixing must be clean.
- Coatings must be done on wetted surface only.
- Harsh and vigorous use of sand or emery paper should be avoided.



PACKAGING SIZES 20 Kg & 40 kg.



DEVELOPED & MARKETING BY: Milap Niketan, Bhadur Shah Zafar Marg, New Delhi – 110002 Ph.: 011-33001142,33001112. Fax: 011-23722251.

Website: www.jklakshmicement.com Helpline No.: 18001025097, Email: jklc.customercare@jklmail.com

