



JK LAKSHMI PRIMER

SMART INTERIOR WALL PRIMER



सुंदरता गारंटीड

JK Lakshmi Smart Interior Wall Primer is a water-based undercoat that provides an ideal finish to the interior walls subsequent to the finishing paint. It blocks out stains and odours, seals the wall, and provides a smooth surface.

PRODUCT BENEFITS



Excellent Coverage
120 to 140 sq ft/ltr



Ultra-White &
Opaque with
Smooth Finish



Does Not Chalk
and Can Be Applied
on Adequately Cured
Fresh Plaster



Gives Superb
Adhesion to Top
Coat Emulsion



Excellent Top
Coat Appearance



0% Water Curing
Required

PRODUCT FEATURES

- 100% acrylic latex & co-polymer based.
- Low VOC (volatile organic compound).
- Low odour.
- Extra TIO₂ (Titanium Dioxide) added for maximum coverage and increased whiteness.

TECHNICAL SPECIFICATIONS

- Coverage-120-140 sq ft/ltr
- Drying Time – 4-5 Hrs
- Flash Point-NA
- Specific Gravity-1.4
- Pot Life-24 Hrs
- Shelf Life-24 months from the date of manufacture in original tightly closed containers away from sunlight & excessive heat.

AREAS OF USAGE

- Interior & Exterior Cement Plaster
- Concrete
- Asbestos Sheets
- Ceilings
- Existing Painted Surfaces

DIRECTIONS FOR USE

- Smoothly prepare the surface, then wipe it clean and dry.
- JK Lakshmi Smart Interior Wall Primer can be thinned with water in 1:1 ratio by volume.
- Apply 1st coat & allow to dry for 4-5 hours.
- If needed, smoothen the surface again & let it dry for 4-5 hours.
- Apply next coat of primer & get a smart finish to reduce consumption of top coat.
- Allow it to dry for 3-4 hours, make it smooth & now surface is ready for the top coat.

FOR BEST RESULTS: Before applying primer, prepare the surface by using
Available in 1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr *Subject to availability.

Customer Helpline: 1800 102 5097 www.jklakshmicement.com

www.instagram.com/jklakshmicementofficial

www.facebook.com/JKLakshmiCementLtd





JK LAKSHMI PRIMER

SMART EXTERIOR WALL PRIMER



सुंदरता गारंटीड

JK Lakshmi Smart Exterior Wall Primer is a water-based undercoat to emulsions suitable for exterior walls.


PRODUCT BENEFITS



Excellent Coverage
120 to 140 sq ft/ltr



Ultra-White &
Opaque with
Smooth Finish



Does Not Chalk
and Can Be Applied
on Adequately Cured
Fresh Plaster



Gives Superb
Adhesion to Top
Coat Emulsion



Excellent Top
Coat Appearance



0% Water Curing
Required

PRODUCT FEATURES

- 100% acrylic latex & co-polymer based.
- Low VOC (volatile organic compound).
- Low odour.
- Extra TIO₂ (Titanium Dioxide) added for maximum coverage and increased whiteness.

TECHNICAL SPECIFICATIONS

- Coverage-120-140 sq ft/ltr
- Drying Time – 3-4 Hrs
- Flash Point-NA.
- Specific Gravity-1.4
- Pot Life-24 Hrs
- Shelf Life-24 months from the date of manufacture in original tightly closed containers away from sunlight & excessive heat.

AREAS OF USAGE

- Interior & Exterior Cement Plaster
- Concrete
- Asbestos Sheets
- Ceilings
- Existing Painted Surfaces

DIRECTIONS FOR USE

- Smoothly prepare the surface, then wipe it clean and dry.
- JK Lakshmi Smart Exterior Wall Primer can be thinned with water in 1:1 ratio by volume.
- Apply 1st coat & allow to dry for 3-4 hours.
- If needed, smoothen the surface again & let it dry for 3-4 hours.
- Apply next coat of primer & get a smart finish to reduce consumption of top coat.
- Allow it to dry for 3-4 hours, make it smooth & now surface is ready for the top coat.

FOR BEST RESULTS: Before applying primer, prepare the surface by using
Available in 1 Ltr, 4 Ltr, 10 Ltr, 20 Ltr *Subject to availability.

Customer Helpline: 1800 102 5097 www.jklakshmicement.com

www.instagram.com/jklakshmicementofficial

www.facebook.com/JKLakshmiCementLtd

